

# BITUTHENE<sup>®</sup> Primer WB

Water-based primer for use with Bituthene membranes and underlayment

---

## Product Description

BITUTHENE<sup>®</sup>Primer WB is a non-fibrated, stable, odour and taint-free water-based bituminous primer. It promotes good initial adhesion and more importantly, excellent permanent adhesion of Bituthene membranes.

## Use

Bituthene Primer WB is used to prime many substrates including metal, slate, concrete, asbestos, cement and lightweight concrete screeds on which Bituthene membranes will be applied.

Bituthene Primer WB is used for vertical and horizontal applications at 5 °C or above.

## Preparation

Surfaces must be dry and clean, free from dust, dirt, grease, moss or any other foreign matter.

## Application

Bituthene Primer WB is packaged ready to use. Do not dilute with water or solvent. Bituthene Primer WB can be used by roller, brush-applied or spray-applied to damp (not wet) or dry clean surface. Ensure that only an even, thin coating is applied and ensure Bituthene Primer WB has fully penetrated the substrate. Prime twice if substrate is porous. Stir emulsion well before use.

Application coverage rate is 0.5 and 0.8L / m<sup>2</sup> per coat. Estimated coverage for concrete, cement sand screed surfaces is 0.3 and 0.5L / m<sup>2</sup> per coat. Actual measurement may vary due to the condition of the substrate. This information is only a guide.

Allow the primer to dry one to two hours under normal condition. In humid conditions, drying time may be longer. Generally, priming should be limited to what can be covered in 24 hours. In conditions where long drying times are expected, substrates may be primed in advance. Substrates should be reprimed if significant dirt or dust accumulates.

## Supply

Pack Size	20 litre pail
Storage	Dry conditions below +30oC
Shelf Life	12 months in unopened condition

## Cleaning

Before primer dries, tools should be cleaned with water. After primer dries, tools should be cleaned with Paraffin (Kerosene) or White Spirit. During work, place tools in water when not in use. Do not use solvents to clean hands or skin.

## Health and Safety

Read the product label and Material Safety Data Sheet before use. Users must comply with all risk and safety phrases.

## Technical Services

For assistance with working drawings for projects and additional technical advice, please contact your local GCP representative.

[gcpat.hk](http://gcpat.hk) | For technical information: [enquiry.hk@gcpat.com](mailto:enquiry.hk@gcpat.com)

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

Bituthene is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies, Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2016 GCP Applied Technologies, Inc.

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Alpharetta, GA 30009, USA

GCP (Hong Kong) Ltd., 6 On Chuen Street, On Lok Tsuen Ind Area, Fanling, Hong Kong

This document is only current as of the last updated date stated below and is valid only for use in Hong Kong. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on [www.gcpat.hk](http://www.gcpat.hk). Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2025-07-21

[gcpat.hk/solutions/products/bituthene-post-applied-waterproofing/bituthene-primer-wb](http://gcpat.hk/solutions/products/bituthene-post-applied-waterproofing/bituthene-primer-wb)